

YSL12M CC SERIES

Input: 100-240VAC 50/60Hz; 200-240VAC 50Hz

Output Current: depend on requirement

Rated Power: 6W max



Features:


- Universal Input:
100-240V AC 50/60Hz; 200-240VAC 50Hz
- RoHS Compliance
- EMI Standard EN55015:2019+A11
- Safety Standard: EN61347-1:2015, EN61347-2-13:2014+A1:2017, UL8750
- Inrush current < 65A AC230V/50Hz
- High efficiency & low power consumption
- Short Circuit, Over Current and Over Voltage Protection
- Over temperature protection
- 100% full load burn-in test

Application:

LED lights bring
LED indoor lighting
LED decorative lighting
LED building lighting



■ Dimensions and Installation



YSL12M CC SERIES

MODEL DETAIL SPEC. (Allow for customized)		YSL12M-350	YSL12M-500	YSL12M-700
INPUT	Input Voltage:	100-240VAC/200-240VAC		
	Input Frequency:	50/60Hz		
	Inrush Current:	65A/230VAC at full load		
	AC Current:	0.087A/115VAC 0.043A/230VAC		
	Leakage Current:	< 0.25mA/240VAC		
	Efficiency:	88%		
OUTPUT	Rated Current:	350mA	500mA	700mA
	Voltage Range:	10-17V	7-12V	5-8.5V
	Rated Power:	6W		
	Current Tolerance:	±5.0%		
	Ripple and Noise:	<5%	<5%	<5%
	Line Regulation:	±3%		
	Load Regulation:	±5%		
	Setup, Rise, Hold Up time:	1s, 10ms/60ms 230VAC 1000ms, 1ms/25ms 115VAC at full load		
ENVIRONMENTAL	Operating Temperature:	-20 ~ +50 (Refer to "Derating Curve")		
	Storage Temp:	-40°C ~ 85°C		
	Storage Humidity:	20 ~ 95% RH		
	Working Humidity:	20 ~ 95% RH non-condensing		
PROTECTION	Over Load:	Above 105%-130% rated output power		
		Protection type: Hiccup mode, recovers automatically after fault condition is removed		
	Over Voltage:	Above 105%-130% rated output voltage		
		Protection type: Shut down o/p voltage, re-power on to recover		
	Over Temperature:	Shut down o/p voltage, re-power on to recover		
SAFETY & EMC	Safety Regulations:	EN61347-2-13:2014+A1:2017, EN61347-1:2015; EN62493:2015		
	Withstand Voltage:	I/P-O/P: 3.75KVAC		
	Harmonic	EN61000-3-2 Class C EN61000-3-3		
	EMI:	Compliance to EN55015		
	EMS :	compliance to 61547:2009		
OTHER	MTBF:	200,000 Hours Minimum at Full Load at 25°C Ambient		
	Size:	132*52*12mm		
	Weight:	150g / pcs		
	Packaging:	100PCS/CTN		

YSL12M CC SERIES

Deduction curve and temperature



Environment temperature(°C)

Minus output and input voltage curves



Input voltage(VAC)

Functional Diagram

